



|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Code</b>                      | FLR-CHR-5231K                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Description</b>                       | Exposed Parts of Single Lever Built-in In-wall Manual Valve with Basin Spout, two separate wall flanges and operating lever (Suitable for item ALD-233PSO & ALD-235PSO)                                                                                                                                                                                                                                             |
| <b>Flow Rate</b>                         | 13.60 LPM @ 3 bar                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Flow regulator</b>                    | By using flow regulators (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM & GD-3.8 LPM @ 3.0 Bar pressure) one can regulate the flow rate.                                                                                                                                                                                                                                                          |
| <b>Recommended Water Pressure</b>        | 0.5 Bar - 5 Bar                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Brass Specification in Percentage</b> | <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b><br/>Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p><b>Brass Pipe as per IS:407-1996</b><br/>Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| <b>Finish</b>                            | Plating: Nickel-10.0 micron Chromium-0.3 micron<br>Salt Spray (500 hrs + Validated)<br>Adhesion (Pass)                                                                                                                                                                                                                                                                                                              |
| <b>Aerator Size</b>                      | WRAS, ACS Approved (20X1)                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Available Colour Finishing</b>        | CHROME (CHR)                                                                                                                                                                                                                                                                                                                                                                                                        |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.