



## BATH + LIGHT



### WALL LIGHT 12W


12W Down Dolby 2 LED Wall Light

Outdoor Luminaire

Product Code:

457LL12X1H.NHG

12W - 720lm - 3000K - CRI>70 Ra - Beam Angle - 45°



### Technical Specifications

Operating Temperature	-10°C to 45°C
Rated Input Voltage & Frequency	220-240 V AC
Rated Input Wattage	12W ± 10%
Rated Input Current	0.060 Amp (Nominal)
Power Factor	>0.9
ATHD	<20%
Rated Luminous Flux	720 lm (tolerance as per BIS)
Rated Luminaire Efficacy	60 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>70 Ra
Beam Angle	45° (within the permissible limits)
Driver Efficiency	≥80%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	Die Cast Aluminium with Powder Coating
Lens / Reflector	PMMA and Glass Transparent Diffuser
Mounting	Wall



### Protections

Over Voltage Protection	Withstand upto 300V (for 20 min)
Surge Protection	±2.0KV
Ingress Protection (IP Rating)	IP65
Impact Protection (IK Rating)	IK08
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

## Product Dimensions (L x W x H)

196 X 138 X 85 mm (Tol.±5 mm)



## Applications

Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.